

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: NUTRACID PRIMER PART A  
PRODUCT CODES: 22878

MANUFACTURER: Garon Products Inc.  
STREET ADDRESS: PO Box 1924  
CITY, STATE, ZIP: Wall, NJ 07719

INFORMATION PHONE: 732-223-2500  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Novolac/solvent mixture

---

## SECTION 2: HAZARDS IDENTIFICATION

---

### Hazard Overview

GHS Classification: Flammable liquid category 3, Specific target organ toxicity – single exposure category 3, Skin corrosion/irritation category 2, skin sensitizer category 1B, Serious eye irritation category 2B, Acute hazard to aquatic environment category 3

GHS Label Elements and Precautionary Statements:

Label Elements: Flame, Exclamation Mark



### Hazard Statements:

Warning: Flammable liquid and vapor.  
Warning: May cause drowsiness or dizziness  
Warning: Causes skin irritation  
Warning: May cause an allergic skin reaction  
Warning: Causes serious eye irritation.  
Harmful to aquatic life.

### Precautionary statements:

P102 Keep out of reach of children.  
P103 Read label before use  
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area.  
P264 Wash hands thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.  
P370 + P378 In case of fire: Use FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL for extinction.  
P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell  
P302 + P352 IF ON SKIN: wash with plenty of soap and water.  
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.  
P362 + P364 take off contaminated clothing and wash it before reuse.  
P302 + P352 IF ON SKIN: wash with plenty of soap and water.  
P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 IF eye irritation persists: Get medical advice/attention.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

## SAFETY DATA SHEET

P233 Keep container tightly closed.

**Disposal:**

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

Other Non-classifiable potential hazards:

Carcinogen category 2

**HMIS HAZARD CLASSIFICATION**

HEALTH: 2      FLAMMIBILITY: 3      REACTIVITY: 0      PERSONAL PROTECTIVE EQUIPMENT: G

**POTENTIAL HEALTH EFFECTS**

EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING OR BLURRED VISION.

SKIN: MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.

INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA AND ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

INHALATION: CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS

HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATION OF VAPOR. OVER-EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITIES, ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE OR EVEN EYE DAMAGE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS

CARCINOGENICITY

OSHA: NO      NTP: NO      IARC: YES

ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation Of Carcinogenicity: IARC MONOGRAPHS ON EVALUATION

OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B. 2BTitanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

---

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

---

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
MODIFIED DIGLYCIDYL ETHER OF BISPHENOL A	25068-38-6	NONE	NONE	NONE	3-7
ALKYL GLYCIDYL ETHER	68609-97-2	NONE	NONE	NONE	0.1-1
Epoxy phenol novolac resin	28064-14-4	NONE	NONE	NONE	10-30
BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN	9003-36-5	NONE	NONE	NONE	30-60
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	100 PPM	100 PPM	150 PPM	10-30
Siloxanes and silicones, di-me reactions products with Silica (non-hazardous)	67762-90-7	NONE	NONE	NONE	0.1-1
siloxanes and silicones, di-methyl (non-hazardous)	63148-62-9	NONE	NONE	NONE	0.1-1
STODDARD SOLVENT	8052-41-3	100PPM	100 PPM	NONE	0.1-1
1-Methoxy-2-Propanol Acetate	108-65-6	50PPM	NONE	NONE	0.1-1
*1,2,4-Trimethylbenzene	95-63-6	25PPM	NONE	NONE	(0.5%)
sec-butyl alcohol	78-92-2	150PPM	100PPM	NONE	0.1-1
acetic acid, butyl ester	123-86-4	150PPM	150PPM	200PPM	0.1-1

Colors may contain @ 7-13%:

Titanium Dioxide	13463-67-7	10mg/m <sup>3</sup>	10mg/m <sup>3</sup>	5mg/m <sup>3</sup>	
*CARBON	1333-86-4	3.5PPM	3.4PPM	NONE	<1.0
Precipitated Silica	112926-00-8	NONE	80mg/m <sup>3</sup>	NONE	
Iron III oxide	1309-37-1	10mg/m <sup>3</sup>	5mg/m <sup>3</sup>	NONE	
Yellow Pigment	Not available	NONE	NONE	NONE	
Zinc Sulfide (component of yellow pigment)	1314-98-3	NONE	NONE	NONE	
Barium Sulfate (component of yellow pigment)	7727-43-7	NONE	NONE	NONE	
Titanium Dioxide (component of yellow pigment)	13463-67-7	NONE	NONE	NONE	
Pigment yellow 65 (component of yellow pigment)	6528-34-3	NONE	NONE	NONE	
Iron III hydroxide	20344-49-4	15mg/m <sup>3</sup>	5mg/m <sup>3</sup>	NONE	
C.I. Pigment Blue	147-14-8	1mg/m <sup>3</sup>	1mg/m <sup>3</sup>	NONE	
Aluminum Oxide	1344-28-1	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>	NONE	
Silica, amorphous	7631-86-9	80mg/m <sup>3</sup>	10mg/m <sup>3</sup>	NONE	
Iron Oxide Yellow	51274-00-1	15mg/m <sup>3</sup>	10mg/m <sup>3</sup>	NONE	
Silica, amorphous	7631-86-9	80mg/m <sup>3</sup>	10mg/m <sup>3</sup>	NONE	

SECTION 3 NOTES: \*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

---

## SECTION 4: FIRST AID MEASURES

---

EYES: FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN: SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION: LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE CONSULT WITH A PHYSICIAN.

INHALATION: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

FLAMMABLE LIMITS IN AIR, UPPER: not available  
(% by volume) LOWER: not available

FLASH POINT: 89+°F

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO<sub>2</sub>, DRY CHEMICAL,

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. PRESENCE OF SOLVENTS IN PRODUCT MAY REQUIRE GROUNDING.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

IF FIRE OCCURS, SOLVENTS MAY PRODUCE EXCESSIVE PRESSURE. SEALED DRUMS MAY RUPTURE AND IGNITE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND IGNITE BY ANY SOURCE OF IGNITION. NEVER USE A CUTTING OR WELDING TORCH NEAR CONTAINERS (EVEN EMPTY). ALL 5 GALLON AND LARGER CONTAINERS SHOULD BE GROUNDED BEFORE TRANSFERRING MATERIAL.

---

## SECTION 6: RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

---

## SECTION 7: HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS. KEEP MATERIAL AWAY FROM ALL SOURCES OF IGNITION.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT.

WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILATION IS NOT SUFFICIENT TO CONTROL VAPORS.

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK AND EXPOSURE.

VENTILATION:

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TOXIC LEVEL VALUES.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID VARYING COLORS  
BOILING POINT OR RANGE: 200 TO 392F  
VAPOR DENSITY (AIR = 1): Not available  
SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 1.2  
EVAPORATION RATE: not available  
SOLUBILITY IN WATER: NEGLIGIBLE  
ODOR THRESHHOLD: N/A  
PH: N/A  
MELTING POINT/FREEZING POINT: N/A  
VAPOR PRESSURE: N/A  
AUTO IGNITION TEMPERATURE: N/A  
PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A  
DECOMPOSITION TEMPERATURE: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

STABILITY:  
STABLE  
CONDITIONS TO AVOID (STABILITY):  
AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITION SUCH AS SPARKS, HEATERS, STATIC DISCHARGES ETC..  
INCOMPATIBILITY (MATERIAL TO AVOID):  
AVOID AMINE CURING AGENTS IN UNCONTROLLED AMOUNTS AND STRONG OXIDIZING AGENTS.  
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:  
MAY FORM TOXIC CHEMICALS, CARBON DIOXIDE, CARBON MONOXIDE AND VARIOUS HYDROCARBONS ETC..  
HAZARDOUS POLYMERIZATION:  
WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)  
Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes  
Component Epoxy phenol novolac resin CAS# 28064-14-4: LD50 Oral: >4000 mg/kg (adult rat). LD50 skin (adult rabbit) >2000 mg/kg. Mutagenicity was negative in in-vivo genotoxicity assays. Mixed results were seen in in-vitro genotoxicity assays.  
Component BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN CAS# 9003-36-5: Acute Oral Effects: LD50 (rat) >5000 mg/kg. Acute Dermal Toxicity (rabbit) >3000 mg/kg. Inhalation toxicity LC50 (rat) >1.7 mg/l air for a 4-hr aerosol exposure (maximum concentration obtained). Sensitization (guinea pig) causes sensitization. Skin Irritation (rabbit) Causes moderate irritation. Eye irritation (rabbit) Causes slight irritation.  
Component CAS# 107-98-2: Ingestion LD50 rat 4016 mg/kg, Dermal LD50 rabbit >2000 mg/kg, Inhalation LC50 6 hr. Vapor, rat >25.8 mg/l. May cause eye or skin irritation. May effect Kidney or liver. Has been reported to be toxic to fetus in laboratory animals.  
Component CAS# 8052-41-3: Draize test (rabbit) eye: 500 mg/24hr – Moderate. Epidemiology: Studies involving petroleum refinery workers indicate that persons with routine exposure to petroleum based constituents may be at an increased risk to the development of benign neoplasms, digestive tract cancer and skin cancer. LD50 oral >6000 mg/kg (rat). Dermal LD50 >3000 mg/kg (rabbit). Inhalation LC50 = 5500 mg/kg (4 hr.) (rat). Component is a moderate skin irritant. Product is an eye irritant.  
Component CAS# 108-65-6: Oral LD50 = 8532 mg/kg (rat). Dermal LD50 >5000 mg/kg (rabbit). Inhalation LC50 >100ppm (4hr) (rat) Component is a moderate skin irritant. Product is an eye irritant  
Component CAS# 95-63-6: Oral LD50 (rat) = 5000 mg/kg. Inhalation LC50 (rat) -4h = 18000 mg/m<sup>3</sup>.  
Component CAS# 78-92-2: Acute Oral Toxicity LD50 = 6480 mg/kg (rat)  
Component acetic acid, butyl ester CAS# 123-86-4: Acute Oral Toxicity LD50 = 10768 mg/kg (rat) 4hr estimated. Acute Dermal Toxicity LD50 = 17601 mg/kg (rabbit) 4hr estimated. Acute Toxicity of the vapor LC50 = 2000 (rat) 4hr estimated.  
Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.  
Component CAS# 67762-90-7: LD50 (rat >1000 mg/kg, LD50 dermal (rabbit) >2000 mg/kg  
Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg  
Component CAS# 112926-00-8: LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg  
Component Iron III oxide CAS# 1309-37-1: Acute Oral Toxicity LD50 >5000 mg/kg (rat). Acute Dermal Toxicity LD50 >5000 mg/kg (rat)  
Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.. Acute oral value of 20 gm/kg or greater in rats  
Component Iron III hydroxide CAS# 20344-49-4: Acute Oral Toxicity LD50 >5000 mg/kg (rat).

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l. Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component Epoxy phenol novolac resin CAS# 28064-14-4: Freshwater Fish Toxicity - the acute LC50 is 1-10 mg/L, based on similar materials; Freshwater Invertebrates. Toxicity - the acute EC50 is 1-10 mg/L, based on similar materials. Material is not readily biodegradable.

Component CAS# 107-98-2: Bioconcentration potential is low (BCF less than 100). Potential for mobility in soil is high (KOC between 0 and 50). Material is readily biodegradable and is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100mg/l in the most sensitive species tested.. LC50 fathead minnow 96 hr. 20800 mg/l, LC50 water flea 48 hr. lethally 23300 mg/l, EbC50 green algae biomass growth inhibition 7 d >1000 mg/l. Toxicity to microorganisms IC50 activated sludge > 1000 mg/l

Component CAS# 95-63-6: Toxicity to fish LC50 (fathead minnow) 7.72 mg/l 96 hr. Toxicity to daphnia and other aquatic invertebrates: Immobilization EC50 (water flea) 3.6mg/l 48hr.

Component CAS# 108-65-6: Biodegradation Aerobic: 100% exposure time 8 days. Acute and prolonged Toxicity to Fish LC50: 161 mg/l (fathead minnow, 96 hrs; Acute toxicity to Aquatic Invertebrates EC50: 408 mg/l (water flea, 48 hrs))

Component CAS# 78-92-2: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. The products of degradation are more toxic.

Component acetic acid, butyl ester CAS# 123-86-4 : Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. The products of degradation are more toxic.

Component Titanium Dioxide: Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

Component CAS# 112926-00-8: Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l

Component Iron III oxide CAS# 1309-37-1 Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Acute toxicity to Aquatic Invertebrates EC0 > 10000 mg/l (water flea). Toxicity to Microorganisms EC0 > 1000mg/l (pseudomonas putida)

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component Iron III hydroxide CAS# 20344-49-4: Acute and Prolonged Toxicity to fish LC0 >1000 mg/l (golden Orfe). Toxicity to Microorganisms EC0 > 10000mg/l (pseudomonas putida)

---

## SECTION 13: WASTE DISPOSAL

---

WASTE DISPOSAL METHOD:.

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

---

## SECTION 14: TRANSPORT INFORMATION

---

DOT: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS PROPYLENE GLYCOL MONOMETHYL ETHER), 3, PG III

IMO/IMDG: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS PROPYLENE GLYCOL MONOMETHYL ETHER), 3, PG III

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component Epoxy phenol novolac resin CAS# 28064-14-4: U.S. Toxic Substances Control Act:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA regulations. Immediate health hazard. The chemical identity of some or all components present is confidential business information (trade secret) and is being withheld as permitted by

29CFR1910.1200 (j). Component is on the Canadian Domestic Substances List (DSL) Canadian WHMIS Class: D2B

Component BISPHENOL F/EPICHLOROHYDRIN EPOXY RESIN CAS# 9003-36-5: Component is on the TSCA and Canada DSL lists. Component is on the New Jersey and Pennsylvania right to know lists

Component CAS# 107-98-2; on the PA right to know list. Product is on the TSCA list and DSL Canada

Component Siloxanes and silicones, di-me reactions products with silica: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component siloxanes and silicones, di-methyl: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component CAS# 8052-41-3: Component is on the TSCA and Canada DSL lists. Component is on the Pennsylvania, California, New Jersey Massachusetts and Minnesota right to know lists.

Component CAS# 95-63-6: This component is subject to SARA Title III Section 313 reporting. This component is in the TSCA and Canada DSL Lists. This component is on the Massachusetts, Pennsylvania, New Jersey right to know lists.

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

Component CAS# 108-65-6: on the TSCA list. Component is on the Pennsylvania, Massachusetts or New Jersey Right to know substance list.  
Component CAS# 78-92-2: Component is on Canada DSL and TSCA lists. Component is on the Massachusetts and Pennsylvania Right to Know list  
Component acetic acid, butyl ester CAS# 123-86-4 : Component is on Canada DSL and TSCA lists. Component is on the Massachusetts and Pennsylvania Right to Know list. n-butyl acetate is a CERCLA hazardous substance  
Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ right to know Regulated chemical List. Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).  
Component Carbon: Contains Proposition 65 Chemicals. Carbon: is listed on TSCA and DSL Canada  
Component CAS# 112926-00-8: Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, TSCA,  
Component Iron III oxide CAS# 1309-37-1 Listed on TSCA Inventory. Section 313/312 hazard category: Chronic health hazard. Potential exposure to all of the California proposition 65 have been determined to be below the No significant risk level (NSRL). Component and its impurities (1%) are on the Pennsylvania, New Jersey right to know substance lists. Component contains the following chemicals listed on the New Jersey and Pennsylvania RTK special hazardous Substance lists: Manganese CAS# 7439-96-5 (0.7%) and Aluminum CAS# 7429-90-5 (0.29%). Component contains the following ingredients which are on the Pennsylvania, Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.075%) and Nickel CAS# 7440-02-0 (0.04%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.04%) and Cobalt CAS# 7440-48-4 (30 ppm).  
Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.  
Component Iron III hydroxide CAS# 20344-49-4: Listed on TSCA Inventory. Potential exposure to all of the California proposition 65 chemicals have been determined to be below the No significant risk level (NSRL). Components are on the Pennsylvania right to know substance list. Component contains the following chemicals listed on the Pennsylvania RTK special hazardous Substance lists: chromium CAS# 7440-47-3 (0.02%) and nickel CAS# 7440-02-0 (0.015%). Component contains the following ingredients which are on the Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.02%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Nickel CAS# 7440-02-0 (0.015%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.015%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Cobalt CAS# 7440-48-4 (70ppm)..  
Component CAS# 147-14-8: Component is on the TSCA List. and not controlled under WHMIS. Component is a CERCLA hazardous substance  
Component CAS# 1344-28-1: Component is on the Massachusetts, New Jersey, Pennsylvania right to know lists. Component is on TSCA list and Canada DSL.  
Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.  
Component CAS# 51274-00-1: Component is on the TSCA list and Canada DSL.  
Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.

---

## SECTION 16: OTHER INFORMATION

---

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**See Section 1 for date of preparation**

## SAFETY DATA SHEET

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: NUTRACID PRIMER PART B  
PRODUCT CODES: 22878

MANUFACTURER: Garon Products Inc.  
STREET ADDRESS: PO Box 1924  
CITY, STATE, ZIP: Wall, NJ 07719

INFORMATION PHONE: 732-223-2500  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Polyamine/solvent mixture

### SECTION 2: HAZARDS IDENTIFICATION

#### Hazard Overview

GHS Classification: Flammable liquid category 3, Specific target organ toxicity – single exposure category 3, Specific target organ toxicity following repeated exposure category 2, Skin corrosion/irritation category 1, skin sensitizer category 1B, Serious eye damage category 1, Acute hazard to aquatic environment category 3, Chronic hazards to aquatic environment category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Corrosion, Health hazard, Flame, Aquatic Toxicity



#### Hazard Statements:

Warning: Flammable liquid and vapor.  
Warning: May cause drowsiness or dizziness  
Warning: May cause damage to organs through prolonged or repeated exposure.  
Danger: Causes Severe skin burns and eye damage  
Warning: May cause an allergic skin reaction  
Danger: Causes serious eye damage.  
Harmful to aquatic life  
Toxic to aquatic life with long lasting effects

#### Precautionary statements:

P102 Keep out of reach of children.  
P103 Read label before use  
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray  
P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.  
P370 + P378 In case of fire: Use FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL for extinction.  
P314 Get medical advice/attention if you feel unwell.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.  
P363 Wash contaminated clothing before reuse.  
P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
P310 Immediately call a POISON CENTER or doctor/physician.  
P321 If skin irritation or burns develop, Call a doctor/physician.

## SAFETY DATA SHEET

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302 + P352 IF ON SKIN: wash with plenty of soap and water.  
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.  
P362 + P364 take off contaminated clothing and wash it before reuse.  
P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 If in eyes, immediately call a POISON CENTER or doctor/physician.  
P391 Collect spillage.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P233 Keep container tightly closed.

**Disposal:**

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

**HMIS HAZARD CLASSIFICATION**

HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

**POTENTIAL HEALTH EFFECTS****EYES:**

CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, OR BLURRED VISION.

**SKIN:**

MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS.

**INGESTION:**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA, AND ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION:**

CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE NAUSEA, HEADACHE, AND POSSIBLE UNCONSCIOUSNESS.

**HEALTH HAZARDS (ACUTE AND CHRONIC):**

AMINE RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. OVER-EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITIES, ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE OR EVEN EYE DAMAGE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

**CARCINOGENICITY**

OSHA: NO NTP: NO IARC: NO

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

---

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

---

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE	15-40
METHYLENEDI (CYCLOHEXYLAMINE)	1761-71-3	NONE	NONE	NONE	10-30
Cyclohexanamine, 4,4-methylenebis reaction products	129733-57-9	NONE	NONE	NONE	10-30
3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE	2855-13-2	NONE	NONE	NONE	10-30
2-HYDROXYBENZOIC ACID	69-72-7	NONE	NONE	NONE	1-5
PROPYLENE GLYCOL MONOMETHYL ETHER	107-98-2	100 ppm	100 ppm	150 ppm	10-30

\*INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

---

**SECTION 4: FIRST AID MEASURES**

---

**EYES:** IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

**SKIN:** FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

**INGESTION:** DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

**INHALATION:** REMOVE TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.



# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

FLAMMABLE LIMITS IN AIR  
(% BY VOLUME)

UPPER: NA  
LOWER: NA

FLASH POINT: 90°F

METHOD USED: SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO<sub>2</sub>, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. PRESENCE OF SOLVENTS IN PRODUCT MAY REQUIRE GROUNDING.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

IF FIRE OCCURS, SOLVENTS MAY PRODUCE EXCESSIVE PRESSURE. SEALED DRUMS MAY RUPTURE AND IGNITE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND IGNITE BY ANY SOURCE OF IGNITION. NEVER USE A CUTTING OR WELDING TORCH NEAR CONTAINERS (EVEN EMPTY). ALL 5 GALLON AND LARGER CONTAINERS SHOULD BE GROUNDED BEFORE TRANSFERRING MATERIAL.

---

## SECTION 6: RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

---

## SECTION 7: HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS; THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS. KEEP MATERIAL AWAY FROM ALL SOURCES OF IGNITION.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT.

WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF

WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILATION IS NOT SUFFICIENT TO CONTROL VAPORS.

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK AND EXPOSURE.

VENTILATION:

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TOXIC LEVEL VALUES.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID – Colored with /SOLVENT ODOR

BOILING POINT OR RANGE: 243 TO 477° F

VAPOR DENSITY (AIR = 1): not available

SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 1.0

EVAPORATION RATE: not available

SOLUBILITY IN WATER: negligible

ODOR THRESHHOLD: N/A

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

PH: N/A  
MELTING POINT/FREEZING POINT: N/A  
VAPOR PRESSURE: N/A  
AUTO IGNITION TEMPERATURE: N/A  
PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A  
DECOMPOSITION TEMPERATURE: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

STABILITY:  
STABLE  
CONDITIONS TO AVOID (STABILITY):  
AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITIONS SUCH AS SPARKS, HEATERS, STATIC DISCHARGES ETC..  
INCOMPATIBILITY (MATERIAL TO AVOID):  
AVOID EPOXY CURING AGENTS IN UNCONTROLLED AMOUNTS AND STRONG OXIDIZING AGENTS.  
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:  
MAY FORM TOXIC CHEMICALS, CARBON DIOXIDE, CARBON MONOXIDE AND VARIOUS HYDROCARBONS ETC..  
HAZARDOUS POLYMERIZATION:  
WILL NOT OCCUR

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

No data for the product itself.  
Component data:  
Components BENZYL ALCOHOL CAS# 100-51-6, METHYLENEDI (CYCLOHEXYLAMINE) CAS# 1761-71-3, Cyclohexanamine, 4,4-methylenebis reaction products CAS# 129733-57-9: LD50 > 2000 mg/kg Species rat – method estimated.  
Component Benzyl Alcohol: Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed Adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.  
Component CAS# 2855-13-2: Oral LD50 rat 1030 mg/kg, Skin irritation – Corrosive subcategory 1C where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days. Eye irritation – Risk of serious damage to eyes. Product Sensitization (Magnusson- Kingman test) guinea pig: may cause sensitization by skin contact. Product Teratogenicity oral rat NOEL (no observed effect level) 250 mg/kg  
Component CAS# 69-72-7: Acute Oral Toxicity LD50 (rat) = 891 mg/kg (behavioral somnolence (general depressed activity, Behavioral muscle weakness)). Acute Inhalation LC50 (rat) >900 mg/m3, 1 hr. Acute Dermal LD50 (rabbit) >10,000 mg/kg. Skin Irritation (rabbit) – mild skin irritation -24hr. Eye Irritation (rabbit) – severe eye irritation.  
Component CAS# 107-98-2: Ingestion LD50 rat 4016 mg/kg, Dermal LD50 rabbit >2000 mg/kg, Inhalation LC50 6 hr. Vapor, rat >25.8 mg/l. May cause eye or skin irritation. May effect Kidney or liver. Has been reported to be toxic to fetus in laboratory animals.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data for the product itself.  
Component data:  
Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD<sub>2</sub> 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr.) 10 mg/l Bluegill sunfish (Lepomis macrochinus), LC50 (96hr) 460 ml/l Fathead minnow (Pimephales promelas), Toxicity to Algae: IC50 (72hr) 700 mg/l  
Component METHYLENEDI (CYCLOHEXYLAMINE) CAS# 1761-71-3: LC50 (96hr) 46-100 mg/l (species golden orfe). EC50 (48hr) 6.84 mg/l (species Daphnia magna). IC50 (72hr) 140-200 mg/l (species algae)  
Component Cyclohexanamine, 4,4-methylenebis reaction products CAS# 129733-57-9: LC50 (96hr) 7.8 mg/l (species rainbow trout)  
Component CAS# 2855-13-2: Biodegradability 42% and is not readily biodegradable. Bioaccumulation: - no significant accumulation of the substance in organisms is to be expected. Mobility: The soil mobility of the substance is only minimally affected by adsorption to soil components. Toxicity to fish: LC50 Lauciscus idus 110 mg/l (96hr). Toxicity to Daphnia NOEC 3 mg/l (504hr). EC50 Daphnia magna 23 mg/l (48 hr.). ErC50 Scenedesmus subspicatus 50 mg/l (72 hr.). NOEC Scenedesmus subspicatus 1.5 mg/l (72 hr.). Toxicity to bacteria: EC10 Pseudomonas putida 1120 mg/l (18 hr.).  
Component CAS# 69-72-7: Toxicity to Fish LC50 (Leuciscus idus – 96 mg/l. Toxicity to Daphnia magna – 105mg/l, 24 hr. Component Mutagenic Effects: Mutagenic for bacteria and/or yeast. Developmental toxicity: Classified reproductive system toxin/female, development toxin possible.  
Component CAS@ 107-98-2: Bioconcentration potential is low (BCF less than 100). Potential for mobility in soil is high (KOC between 0 and 50). Material is readily biodegradable and is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100mg/l in the most sensitive species tested.. LC50 fathead minnow 96 hr. 20800 mg/l, LC50 water flea 48 hr. lethally 23300 mg/l, EbC50 green algae biomass growth inhibition 7 d >1000 mg/l. Toxicity to microorganisms IC50 activated sludge > 1000 mg/l

---

## SECTION 13: WASTE DISPOSAL

---

WASTE DISPOSAL METHOD:  
DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

# SAFETY DATA SHEET

# GARON

PRODUCT CODE: 22878

---

## SECTION 14: TRANSPORT INFORMATION

---

DOT: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS PROPYLENE GLYCOL MONOMETHYL ETHER), 3, PG III

IMO/IMDG : UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS PROPYLENE GLYCOL MONOMETHYL ETHER, METHYLENEDI (CYCLOHEXYLAMINE)), 3, PG III, MARINE POLLUTANT

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

Component data:

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada.

Components METHYLENEDI (CYCLOHEXYLAMINE) CAS# 1761-71-3, Cyclohexanamine, 4,4-methylenebis reaction products CAS# 129733-57-9: Included on TSCA, EINECS, AICS, ENCS, ECL, SEPA lists. Canada DSL – not on inventory, Notifications have been submitted to Environment Canada.

Component CAS# 2855-13-2: Acute health hazard. Ingredients on TSCA. International Chemical status listed/registered – EINECS/ELINCS, DSL, AICS, MITI, TCOL, PICCS, China, New Zealand.

Component CAS# 69-72-7: Component is on the Pennsylvania and New Jersey right to know lists. Component is on the TSCA and Canada DSL lists.

Component CAS# 107-98-2; on the PA right to know list. Product is on the TSCA list and DSL Canada

---

## SECTION 16: OTHER INFORMATION

---

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**See Section 1 for date of preparation**