

SAFETY DATA SHEET



PRODUCT CODE: 15370

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: POUR N WALK PART A
PRODUCT CODES: 15370

MANUFACTURER: Garon Products Inc.
STREET ADDRESS: PO Box 1924
CITY, STATE, ZIP: Wall, NJ 07719-1924

INFORMATION PHONE: 800-631-5380
EMERGENCY PHONE: Chemtrec 800-424-9300
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Epoxy mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Flammable liquids category 4, Skin corrosion/irritation category 2, serious eye irritation category 2A, skin sensitizer category 1, Long term hazards to aquatic environment Category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Aquatic Toxicity

Hazard Statements:

Warning: Combustible liquids.

Warning: Causes skin irritation

Warning: Causes serious eye irritation

Warning: May cause an allergic skin reaction

Toxic to aquatic life with long lasting effects

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

Response:

P370 + P378 In case of fire: Use FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL, WATER FOG for extinction.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

Other Non-classifiable potential hazards

Carcinogen category 2

HMS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMIBILITY: 2 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES: MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

SKIN: MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE. NOT LIKELY TO BE ABSORBED IN TOXIC AMOUNTS.

INGESTION: THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION: NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES.

SAFETY DATA SHEET

HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

CARCINOGENICITY

OSHA: NO NTP: YES IARC: YES

ADDITIONAL CARCINOGENICITY INFORMATION:

Some colors may contain carbon black - Explanation of Carcinogenicity for carbon: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2BTitanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B). Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (group 2B).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
Reaction Products of Epichlorohydrin					
Bisphenol A	25068-38-6	NONE	NONE	NONE	60-100
Alkyl Glycidyl Ether	68609-97-2	NONE	NONE	NONE	10-30
*Xylene	1330-20-7	100PPM	100PPM	150PPM	<0.5%
2, 6-Dimethyl-4-Heptanone	108-83-8	25PPM	25PPM	NONE	0.1-1
*Ethyl benzene	100-41-4	100PPM	100PPM	125PPM	<0.1%
Butyl Acetate	123-86-4	150PPM	150PPM	200PPM	0.1-1
1, 2-Propanediol	57-55-6	NONE	NONE	NONE	0.1-1
*Isobutyl Alcohol	78-83-1	50PPM	50PPM	NONE	<0.5%
Salts from Alkylamides and Esters (NJTSRN 800963-5040)	Trade Secret	NONE	NONE	NONE	0.1-1
<i>Colors May Contain @ 3-7%:</i>					
Titanium Dioxide	13463-67-7	10mg/m ³	10mg/m ³	5mg/m ³	
Carbon Black	1333-86-4	3.5PPM	3.5 PPM	NONE	
Precipitated Silica	112926-00-8	NONE	80mg/m ³	NONE	
Iron III Oxide	1309-37-1	10mg/m ³	5mg/m ³	NONE	
Yellow Pigment	Not available	NONE	NONE	NONE	
Zinc Sulfate (component of yellow pigment)	1314-98-3	NONE	NONE	NONE	
Barium Sulfate (component of yellow pigment)	7727-43-7	NONE	NONE	NONE	
Pigment yellow 65 (component of yellow pigment)	6528-34-3	NONE	NONE	NONE	
Iron III oxide	20344-49-4	15mg/m ³	5mg/m ³	NONE	
C.I. Pigment Blue	147-14-8	1mg/m ³	1mg/m ³	NONE	
Aluminum Oxide	1344-28-1	15mg/m ³	10mg/m ³	NONE	
Silica, amorphous	7631-86-9	80mg/m ³	10mg/m ³	NONE	
Iron Oxide Yellow	51274-00-1	15mg/m ³	10mg/m ³	NONE	
Silica, amorphous	7631-86-9	80mg/m ³	10mg/m ³	NONE	

SECTION 3 NOTES: *Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372. XYLENE ACHIH STEL=150PPM

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

EYES: FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN: SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION: LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, OTHERWISE DO NOT INDUCE VOMITING AND CONSULT A PHYSICIAN.

INHALATION: REMOVE VICTIM TO FRESH AIR AREA AND ADMINISTER OXYGEN IF NECESSARY. CONSULT PHYSICIAN IF NECESSARY.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR UPPER: N/A
(% by volume) LOWER: N/A

FLASH POINT: 178°F

METHOD USED: SETA FLASH

SAFETY DATA SHEET



PRODUCT CODE: 15370

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS, COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NO UNUSUAL FIRE HAZARDS KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFOR, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

VENTILATION:

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERING AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID IN VARYING COLORS

BOILING POINT OR RANGE: 200° TO 279°F

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H₂O = 1): 1.2

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

ODOR THRESHOLD: N/A

pH: N/A

MELTING POINT/FREEZING POINT: N/A

VAPOR PRESSURE: N/A

AUTO IGNITION TEMPERATURE: N/A

PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A

DECOMPOSITION TEMPERATURE: N/A

SAFETY DATA SHEET



PRODUCT CODE: 15370

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES.

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO₂, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

Component CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

Component Titanium Dioxide: Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component CAS# 67762-90-7: LD50 (rat >1000 mg/kg, LD50 dermal (rabbit) >2000 mg/kg

Component Carbon: IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg

Component CAS# 112926-00-8: LD50 (rat >5000 mg/kg, LD50 dermal (rat) >2000 mg/kg

Component Iron III oxide CAS# 1309-37-1: Acute Oral Toxicity LD50 >5000 mg/kg (rat). Acute Dermal Toxicity LD50 >5000 mg/kg (rat)

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200. Acute oral value of 20 gm/kg or greater in rats

Component Iron III oxide CAS# 20344-49-4: Acute Oral Toxicity LD50 >5000 mg/kg (rat).

Component CAS# 108-83-6: Acute oral toxicity LD50 = 5800 mg/kg (rat); Acute dermal toxicity LD50 = 16000 mg/kg (rabbit); Acute inhalation toxicity LC50 = 2000 ppm (rat); Skin irritation – slight irritation (rabbit); Eye irritation – mild eye irritation (rabbit)

Component Xylene: Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may affect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Xylene may contain ethyl benzene. Ethyl benzene has shown limited evidence of a carcinogenic effect.

Component Butyl Acetate: Acute Oral Toxicity LD50 = 10768 mg/kg (rat) 4hr estimated. Acute Dermal Toxicity LD50 = 17601 mg/kg (rabbit) 4hr estimated. Acute Toxicity of the vapor LC50 = 2000 (rat) 4hr estimated.

Component CAS# 57-55-6: LD50 = 20000 mg/kg

Component Isobutyl Alcohol CAS# 78-83-1: LD50 Dermal (rabbit) = 3400 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

No data for the product itself.

Component data:

CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l.

Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

Component Titanium Dioxide: Pimephales Promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50

Component CAS# 112926-00-8: Ecotoxicity: EC50 (fish) .10000 mg/l (daphnia >10000 mg/l)

Component Iron III oxide CAS# 1309-37-1: Acute and Prolonged Toxicity to fish LCO >1000 mg/l (golden Orfe). Acute toxicity to Aquatic Invertebrates ECO > 10000 mg/l (water flea). Toxicity to Microorganisms ECO > 1000mg/l (pseudomonas putida)

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component Iron III oxide CAS# 20344-49-4: Acute and Prolonged Toxicity to fish LCO >1000 mg/l (golden Orfe). Toxicity to Microorganisms ECO > 10000mg/l (pseudomonas putida)

Component Xylene: Acute Toxicity: Fish: Toxic 1 < LCECIC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 < 10mg/l, Algae: Toxic 1 < LC/EC/IC50 < 10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidizes rapidly by photo-chemical reactions in air.

Component Butyl Acetate: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. The products of degradation are more toxic.

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD: DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

SAFETY DATA SHEET



PRODUCT CODE: 15370

SECTION 14: TRANSPORT INFORMATION

DOT: NA1993, COMBUSTIBLE LIQUID N.O.S. (CONTAINS XYLENE, ISOBUTYL ALCOHOL), 3, PG III
IMO/IMDG: UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, ISOBUTYL ALCOHOL, Bisphenol A, Diglycidyl Ether Polymer), 3, PG III, Marine Pollutant

SECTION 15: REGULATORY INFORMATION

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list and is on the PA Right to Know List.

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component Titanium Dioxide: Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, and is on the NJ right to know Regulated chemical List.

Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

Component Carbon: Contains Proposition 65 Chemicals. Carbon: is listed on TSCA and DSL Canada

Component CAS# 112926-00-8: Is not classified as dangerous. National Chemical Inventory listings include – AICS, DSL, IECSC, EINECS, ENCS, KECI, NZLOC, PICCS, and TSCA.

Component Iron III oxide CAS# 1309-37-1 Listed on TSCA Inventory. Section 313/312 hazard category: Chronic health hazard. Potential exposure to all of the California proposition 65 have been determined to be below the No significant risk level (NSRL). Component and its impurities (1%) are on the Pennsylvania, New Jersey right to know substance lists. Component contains the following chemicals listed on the New Jersey and Pennsylvania RTK special hazardous Substance lists: Manganese CAS# 7439-96-5 (0.7%) and Aluminum CAS# 7429-90-5

(0.29%). Component contains the following ingredients which are on the Pennsylvania, Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.075%) and Nickel CAS# 7440-02-0 (0.04%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.04%) and Cobalt CAS# 7440-48-4 (30 ppm).

Component Yellow Pigment: Not Hazardous as defined by OSHA HC Standard 29 CFR 1810.1200.

Component Iron III oxide CAS# 20344-49-4: Listed on TSCA Inventory. Potential exposure to all of the California proposition 65 chemicals have been determined to be below the No significant risk level (NSRL). Components are on the Pennsylvania right to know substance list. Component contains the following chemicals listed on the Pennsylvania RTK special hazardous Substance lists: chromium CAS# 7440-47-3 (0.02%) and nickel CAS# 7440-02-0 (0.015%). Component contains the following ingredients which are on the Massachusetts hazardous substance lists: Chromium CAS# 7440-47-3 (0.02%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Nickel CAS# 7440-02-0 (0.015%) Component contains the following chemicals on the California Proposition 65 list known to the state of California to be carcinogenic: Nickel CAS# 7440-02-0 (0.015%), arsenic CAS# 7440-38-2 (60ppm), Beryllium CAS# 7440-41-7 (1ppm) and Cobalt CAS# 7440-48-4 (70ppm).

Component CAS# 147-14-8: Component is on the TSCA List and not controlled under WHMIS. Component is a CERCLA hazardous substance

Component CAS# 1344-28-1: Component is on the Massachusetts, New Jersey, and Pennsylvania right to know lists. Component is on TSCA list and Canada DSL.

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.

Component CAS# 51274-00-1: Component is on the TSCA list and Canada DSL.

Component CAS# 7631-86-9: Component is on the Minnesota right to know list. Component is on TSCA list and Canada DSL.

Component CAS# 108-83-6: Pennsylvania, Massachusetts and New Jersey Right to Know, (On TSCA, DSL lists)

Component Xylene: Xylene contains EPCRA section 313 chemicals subject to the reporting requirements of the emergency planning and community right to know act of 1968. (Maximum wt. % for components of xylene are: M-Xylene CAS# 108-38-3 is 46%, P-Xylene CAS# 106-42-3 is 20%, Ethyl Benzene CAS# 100-41-4 is 19%, O-Xylene CAS# 95-47-6 is 16%). Xylene and its components are on the California Proposition 65 list for developmental toxicity, Reproductive toxicity and carcinogen list. Ingredients are on the TSCA list, DSL Canada, AICS, China, EINECS, ENCS, Korea, New Zealand, Philippines inventory lists and on the Massachusetts, New Jersey, Pennsylvania right to know lists Ethyl Benzene a component of xylene has been designated by IARC as a possible carcinogen to humans based on increased tumor incidence in laboratory animals. Risk phrases R10 Flammable R20/21 Harmful by inhalation and in contact with skin, R38 irritating to skin, S25 Avoid contact with eyes.

Component Butyl Acetate: Component is on Canada DSL and TSCA lists. Component is on the Massachusetts and Pennsylvania Right to Know list. N-butyl acetate is a CERCLA hazardous substance.

Component CAS# 57-55-6: Listed on TSCA and DSL

Component Isobutyl Alcohol CAS# 78-83-1: Component is on TSCA, EINECS and Canada DSL lists. Section 4 test rules/section 12 export notification for isobutyl alcohol.

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

SAFETY DATA SHEET



PRODUCT CODE: 15370

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: POUR N WALK PART B
PRODUCT CODES: 15370

MANUFACTURER: Garon Products Inc.
STREET ADDRESS: PO Box 1924
CITY, STATE, ZIP: Wall, NJ 07719-1924

INFORMATION PHONE: 800-631-5380
EMERGENCY PHONE: Chemtrec 800-424-9300
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Polyamine Mixture

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Acute oral toxicity category 4, acute dermal toxicity category 4, serious eye irritation/damage category 1, skin sensitizer category 1B, Skin corrosion/irritation category 1, Reproductive toxicity category 2, Acute hazard to aquatic environment category 2
GHS Label Elements and Precautionary Statements: Exclamation Mark, Corrosion, Health Hazard, Aquatic Toxicity

Hazard Statements:

Warning: Harmful if swallowed
Warning: Harmful in contact with skin
Danger: Causes serious eye damage
Warning: May cause an allergic skin reaction
Danger: Causes severe skin burns and eye damage
Warning: Suspected of damaging fertility of the unborn child.
Toxic to aquatic life

Precautionary statements:

P102 Keep out of reach of children.
P103 Read label before use
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves and clothing to prevent skin contact.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection
P273 Avoid release to the environment.

Response:

P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.
P330 Rinse mouth.
P302 + P352 IF ON SKIN: wash with plenty of soap and water
P312 Call a POISON CENTER or doctor/physician if you feel unwell
P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 If in eyes, immediately call a POISON CENTER or doctor/physician.
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
P362 + P364 take off contaminated clothing and wash it before reuse.
P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P405 Store locked up

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

SAFETY DATA SHEET



PRODUCT CODE: 15370

EYES: WILL CAUSE BURNS TO EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.
SKIN: WILL CAUSE BURNS TO THE SKIN
INGESTION: LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.
INHALATION: HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.
HEALTH HAZARDS (ACUTE AND CHRONIC):
PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.
CARCINOGENICITY
OSHA: NO NTP: NO IARC: NO
ADDITIONAL CARCINOGENICITY INFORMATION:
NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
Amino Terminated Polyether	9046-10-0	NONE	NONE	NONE	1-5
Benzyl Alcohol	100-51-6	NONE	NONE	NONE	10-30
1, 2-Cyclohexanediamine	694-83-7	NONE	NONE	NONE	30-60
TRIS-2, 4, 6-Dimethylaminomethylphenol	90-72-2	NONE	NONE	NONE	1-5
Bis (dimethylaminomethyl) phenol	71074-89-0	NONE	NONE	NONE	0.1-1
Nonyl Phenol	84852-15-3	NONE	NONE	NONE	3-7
N-Aminoethylpiperazine	140-31-8	NONE	NONE	NONE	1-5
1-Methoxy-2-Propanol Acetate	108-65-6	NONE	NONE	NONE	1-5
Naphtha-Light Aromatic	64742-95-6	50PPM	400PPM	NONE	1-5
Additive NJTSRN 800963-5061		NONE	NONE	NONE	0.1-1
1, 2, 4-trimethylbenzene	95-63-6	25PPM	NONE	NONE	1-5
2, 6-Dimethyl-4-Heptanone	108-83-8	25PPM	25PPM	NONE	0.1-1
4, 6-Dimethyl-2-heptanone	19549-80-5	NONE	NONE	NONE	0.1-1
Solution of Polyacrylate NJTSRN 800963-549	Trade Secret	NONE	NONE	NONE	0.1-1

SECTION 3 NOTES:

***No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

EYES: FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.
SKIN: FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.
INGESTION: DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.
INHALATION: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.
NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR UPPER: Not Available
(% by volume) LOWER: Not Available

FLASH POINT: 200+°F

METHOD USED: SETA FLASH

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO₂, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

SAFETY DATA SHEET

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID – VARYING COLORS

BOILING POINT OR RANGE: 200° TO 560°F

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H₂O = 1): 1.0

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

ODOR THRESHOLD: N/A

pH: N/A

MELTING POINT/FREEZING POINT: N/A

VAPOR PRESSURE: N/A

AUTO IGNITION TEMPERATURE: N/A

PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A

DECOMPOSITION TEMPERATURE: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO, CO₂, NOX

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component CAS# 9046-10-0: Oral LD50 (rat) = 2880 mg/kg; Dermal LC50 (rabbit) = 2980 mg/kg. Corrosive to skin of rabbit. Severe eye irritation (rabbit)

SAFETY DATA SHEET

GARON

PRODUCT CODE: 15370

Component Benzyl Alcohol: Inhalation LC50 (4hr) >4178 mg/l (rat), Dermal LD50 2000 mg/kg (rabbit) Rats exposed to 800 mg/kg for thirteen weeks exhibited CNS depression and histopathological changes in the brain, thymus and skeletal muscles. The No observed adverse effect level (NOAEL) was 400 mg/kg. No evidence of carcinogenicity was seen in two year study with rats and mice.

Component CAS# 694-83-7: Draize test, rabbit, skin: 500 mg/24H Moderate; Oral, rat: LD50 = 4556 mg/kg;

Component CAS# 90-72-2 and CAS# 71074-89-0: Oral LD50 (rat) 1200 mg/kg; Dermal LD50 (rabbit) 1280 mg/kg; Inhalation LC50 (rat) > 0.5 mg/liter/1 hour; Severe irritant to eyes of a rabbit. Severe irritant to the skin of a rabbit. Corrosive to the skin of a rabbit.

Component Nonyl Phenol: Median Lethal Dose Oral: LD50 0.58g/kg (rat) moderately toxic. Dermal LD50 2.14g/kg (rabbit) slightly toxic. Skin Draize Test, rabbit, 500 mg/m³ 24hr – corrosive. Eyes Draize test rabbit, 57.00/110 – extremely irritating. Component is a possible risk of impaired fertility.

Component CAS# 140-31-8: Draize test, rabbit, eye: 20 mg/24H Moderate; Draize test, rabbit, skin: 5 mg/24H Severe Oral, rat: LD50 = 2140 uL/kg; Skin, rabbit: LD50 = 880 uL/kg; Carcinogenicity: Not listed by ACGIH, IARC, NTP, or CA Prop 65. May cause Sensitization by skin contact.

Component CAS# 64742-95-6: LD50 dermal (rabbit) > 3480 mg/kg. LC50 (4 hr. inhalation, rat) = 5193 ppm.

Component CAS# 108-65-6: LD50 = 8532

Component CAS# 19549-80-5: LD50 oral (rat) > 2300 mg/kg. LC50 (6 hr. inhalation, rat) = 1979 ppm.

SECTION 12: ECOLOGICAL INFORMATION

No data for the product itself.

Component data:

Component Benzyl Alcohol: EC50 (48hr) 400 mg/l Daphnia Magna, EC50 (72hr) 2600 mg/l Algae, Biodegradation BOD2 62. Slightly or not bioaccumulative. Toxicity to fish: LC50 (96 hr.) 10 mg/l Bluegill sunfish (*Lepomis Macrochinus*), LC50 (96hr) 460 ml/l Fathead minnow (*Pimephales Promelas*), Toxicity to Algae: IC50 (72hr) 700 mg/l

Component CAS# 90-72-2 and CAS# 71074-89-0: Toxicity: LC50 fish 447.8 mg/l (96 hr.). LC50 Crust 28.2 mg/l (48 hr.). EC50 alga 34.8 mg/l (96 hr.)

Component Nonyl Phenol: Ecotoxicity: Daphnia EC50: 0.14-0.44 mg/l, 48 hr. Component is not readily biodegradable, log POW: 3-4. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Aquatic Toxicity LC50 96 hr., toxicity rating is <0.10 ppm – extremely toxic

Component CAS# 64742-95-6 Toxic to aquatic organisms.

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD: DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT: UN1760, CORROSIVE LIQUID N.O.S. (N-AMINOETHYLPIPERAZINE, 1, 2-CYCLOHEXANEDIAMINE), 8, PG III

MO/IMDG: UN1760, CORROSIVE LIQUID N.O.S. (N-AMINOETHYLPIPERAZINE, 1,2-CYCLOHEXANEDIAMINE, NONYL PHENOL), 8, PG III, MARINE POLLUTANT

SECTION 15: REGULATORY INFORMATION

No data for the product itself.

Component data:

Component CAS# 9046-10-0: Target organ effects: Corrosive. Component is on the Massachusetts, Pennsylvania, and New Jersey Right to know lists. Component does not contain chemicals known to California (Prop 65) to cause birth defects or other reproductive harm. This component is listed on TSCA, EINECS, ENCS, AICS, ECL, SEPA, PICCS and Canada DSL lists.

Component Benzyl Alcohol: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada

Component CAS# 694-83-7: This component is listed on TSCA, EINECS, ENCS, AICS, ECL, SEPA, and Canada DSL lists.

Component CAS# 90-72-2 and 71074-89-0 EEC symbol – Harmful, harmful if swallowed (R22) Irritating to eyes and skin (R36/38). Component is on the Canada DSL, TSCA, EINECS, AICS, ENCS, ECL, SEPA, PICCS lists

Component Nonyl Phenol: This component is listed on TSCA, EINECS, ACIS, MITI and Canada DSL lists.

Component CAS# 140-31-8: Component is listed on the TSCA inventory. Component can be found on the following state right to know lists: New Jersey, Pennsylvania, and Massachusetts. Component contains no California Prop 65 Significant Risk Level: and none of the chemicals in this product are listed.

Component is list on the Canadian DSL list, EINECS, AICS, ENCS, ECL, SEPA, PICCS lists.

Component CAS# 108-65-6: Listed on TSCA and DSL

Component CAS# 64742-95-6 this product is a hazardous chemical. This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372 Component 1,2,4-trimethylbenzene CAS# 95-63-6 at < 15% and trace amounts of benzene CAS# 71-43-2. Benzene is known to the state of California to cause cancer and birth defects or other reproductive harm and is on the Prop 65 list. Component is on the TSCA and Canada DSL lists Component is on the TSCA list as well as the AICS, DSL, ECL, EINECS, ENCS, IECSC and PICCS lists

Component CAS# 108-83-8: Component is on the TSCA list and Canada DSL.

Component CAS# 19549-80-5: Component is on the TSCA list and Canada DSL.

Component NJTSRN 800963-549: Component is on the TSCA list and Canada DSL.

SAFETY DATA SHEET



PRODUCT CODE: 15370

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation

SAFETY DATA SHEET



PRODUCT CODE: 15370

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: POUR N WALK PART C
PRODUCT CODES: 15370

MANUFACTURER: Garon Products Inc.
STREET ADDRESS: PO Box 1924
CITY, STATE, ZIP: Wall, NJ 07719-1924

INFORMATION PHONE: 800-631-5380
EMERGENCY PHONE: Chemtrec 800-424-9300
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: sand

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Carcinogenicity category 1, Specific target organ toxicity following repeated exposure category 1, Specific target organ toxicity (single exposure) category 3

GHS Label Elements and Precautionary Statements:

Label Elements: Health hazard, Exclamation Mark

Hazard Statements:

DANGER: May cause cancer

DANGER: Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system)

WARNING: May cause respiratory irritation.

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P405 Store locked up

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: E

POTENTIAL HEALTH EFFECTS

EYES: MAY CAUSE REDDENING OF THE EYES OR EYE IRRITATION FROM AIRBORNE PARTICLES.

SKIN: NONE KNOWN

INGESTION: NONE KNOWN

INHALATION: PROLONGED EXPOSURE TO RESPIRABLE CRYSTALLINE QUARTZ MAY CAUSE DELAYED LUNG INJURY (SILICOSIS). ACUTE OR RAPIDLY DEVELOPING SILICOSIS MAY OCCUR IN A SHORT PERIOD OF TIME IN HEAVY EXPOSURE IN SOME APPLICATIONS SUCH AS SAND BLASTING.

HEALTH HAZARDS (ACUTE AND CHRONIC):

MAY CAUSE DELAYED SILICOSIS OR RAPID SILICOSIS IN SOME OCCUPATIONS SUCH AS SANDBLASTING, SILICOSIS IS A FORM OF A DISABLING PULMONARY FIBROSIS WHICH CAN BE PROGRESSIVE AND COULD LEAD TO DEATH. INHALATION MAY LEAD TO LUNG SCARRING AND MASSIVE FIBROSIS WHICH COULD BE ACCOMPANIED BY RIGHT HEART ENLARGEMENT, HEART FAILURE, OR PULMONARY FAILURE, SMOKING AGGRAVATES THE EFFECTS OF EXPOSURE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS CAN BE AGGRAVATED BY EXPOSURE

SAFETY DATA SHEET



PRODUCT CODE: 15370

CARCINOGENICITY

OSHA: NO NTP: YES IARC: YES

ADDITIONAL CARCINOGENICITY INFORMATION:

IARC HAS DETERMINED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ IS CARCINOGENIC TO HUMANS (GROUP 1- CARCINOGENIC TO HUMANS). THE NTP CLASSIFIES RESPIRABLE CRYSTALLINE SILICA AS REASONABLY ANTICIPATED TO BE A CARCINOGEN.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
Silicon Dioxide	14808-60-7	10mg/m ³	.1mg/m ³	.1mg/m ³	100

SECTION 2 NOTES:

***No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

FOLLOW OSHA HAZARD COMMUNICATION RULE 29CFR SECTIONS 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, AND STATE AND LOCAL COMMUNITY RIGHT TO KNOW LAWS. WE RECOMMEND THAT SMOKING BE PROHIBITED IN AREAS WHERE RESPIRATORS MUST BE USED.

SECTION 4: FIRST AID MEASURES

EYES: FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN IF CONDITIONS WARRANT.

SKIN: SKIN CONTACT WILL NORMALLY CAUSE NO HEALTH RISKS

INGESTION: IF INGESTED, CONSULT A PHYSICIAN

INHALATION: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR UPPER: Not Available
(% by volume) LOWER: Not Available

FLASH POINT °F: N/A

METHOD USED: N/A

EXTINGUISHING MEDIA: OTHER

SPECIAL FIRE FIGHTING PROCEDURES:

CRYSTALLINE SILICA IS NEITHER A FIRE NOR AN EXPLOSION HAZARD

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND USE DUSTLESS HANDLING EQUIPMENT TO CLEAN UP LARGE SPILLS, PLACE IN SUITABLE CONTAINERS FOR DISPOSAL. FLUSH AREA WITH WATER AFTER PICKUP OF MATERIAL.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE. PROPERLY LABEL ALL CONTAINERS AND RESEAL ALL PARTIALLY USED CONTAINERS. AVOID CREATING ANY DUST WHEN WORKING WITH THIS MATERIAL.

OTHER PRECAUTIONS:

AVOID BREATHING DUST GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. PROVIDE TRAINING FOR YOUR EMPLOYEES RELATING TO OCCUPATIONAL EXPOSURE TO QUARTZ DUST. SEE ASTM STANDARD E1132-86 STANDARD PRACTICE FOR HEALTH REQUIREMENTS RELATING TO EXPOSURE TO QUARTZ DUST. IF BETTER THAN 500 X PEL USE A SELF CONTAINED BREATHING APPARATUS. IF SANDBLASTING, USE ANY TYPE CE SUPPLIED AIR RESPIRATOR WITH FULL FACE PIECE OR HOOD.

Safety phrases

S22 Do not breathe dust

S25 Avoid contact with eyes

S38 In case of insufficient ventilation wear suitable respiratory equipment

S39 Wear eye/face protection

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

SAFETY DATA SHEET

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO QUARTZ DUST. PROVIDE SUFFICIENT EXHAUST TO KEEP EXPOSURE LEVELS BELOW THE ACGIH PEL.

VENTILATION:

USE EXHAUST SUFFICIENT TO MAINTAIN AIRBORNE PARTICULATES BELOW THE ACGIH PEL LIMITS ESTABLISHED.

PROTECTIVE GLOVES:

N/A

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

PROVIDE ANY EQUIPMENT NECESSARY TO PREVENT THE INHALATION OF QUARTZ DUST.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: WHITE OF TAN SAND GRANULAR CRUSHED OR GROUND- NO ODOR

BOILING POINT OR RANGE °F: N/A

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H₂O = 1): 2.6

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: INSOLUBLE IN WATER

ODOR THRESHOLD: N/A

pH: N/A

MELTING POINT/FREEZING POINT: N/A

VAPOR PRESSURE: N/A

AUTO IGNITION TEMPERATURE: N/A

PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A

DECOMPOSITION TEMPERATURE: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

CONTACT WITH POWERFUL OXIDIZING AGENTS SUCH AS FLUORINE, CHLORINE, TRIFLUORIDE, MANGANESE TRIOXIDE, OXYGEN TRIFLUORIDE

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS- SEE CONDITIONS TO AVOID

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SILICA WILL DISSOLVE IN HYDROCHLORIC ACID TO FORM A CORROSIVE GAS- SILICON TETRAFLUORIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

Silicon dioxide: Inhalation and retention of respirable crystalline silica can cause silicosis in several forms, chronic, accelerated or acute. Acute silicosis can occur with exposures to high concentrations of respirable crystalline silica over a very short time period, the symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis can be fatal. IARC concluded that there was sufficient evidence in humans for the carcinogenicity of crystalline silica in the form of quartz (Group 1). Exposure to respirable crystalline silica can also be associated with autoimmune disease, tuberculosis, kidney damage, non-malignant respiratory disease. For further information, the NIOSH Hazard Review- Occupational Effects of Occupational Exposure to Respirable Crystalline Silica published in April of 2002 should be reviewed.

SECTION 12: ECOLOGICAL INFORMATION

Silicon Dioxide: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD: DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

SECTION 14: TRANSPORT INFORMATION

DOT: Not Regulated

SAFETY DATA SHEET



PRODUCT CODE: 15370

IMO/IMDG Not regulated

SECTION 15: REGULATORY INFORMATION

Silicon Dioxide: risk phrases: R 48/20 Harmful – Danger of serious damage to health by prolonged exposure through inhalation. Safety Phrases: S 22 – Do not breathe dust and S 38 – In case of insufficient ventilation, wear suitable respiratory equipment

Crystalline Silica (Silicon Dioxide) is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Crystalline Silica (Silicon Dioxide) is on the Canada DSL – WHMIS Classification D2A

Crystalline Silica is on the Australian Inventory of Chemicals Substances list, Japan Ministry of International Trade and Industry list, Korea Existing Chemicals Inventory with registry number 9212-5667 and the Philippines Inventory of Chemicals and Chemical Substances list.

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

See Section 1 for date of preparation