

# SAFETY DATA SHEET



PRODUCT CODE: 36802

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: TIGERGROUT HD PART A  
PRODUCT CODES: 36802

MANUFACTURER: Garon Products Inc.  
STREET ADDRESS: PO Box 1924  
CITY, STATE, ZIP: Wall, NJ 07719-1924

INFORMATION PHONE: 800-631-5380  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Epoxy Mixture

---

## SECTION 2: HAZARDS IDENTIFICATION

---

### Hazard Overview

GHS Classification: Serious eye damage/Eye irritation category 2A, Skin irritation category 2, skin sensitizer category 1, Long term hazards to aquatic environment Category 2

GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Aquatic Toxicity

### Hazard Statements:

Warning: Causes serious eye irritation.

Warning: Causes skin irritation

Warning: May cause an allergic skin reaction

Toxic to aquatic life with long lasting effects

### Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

### Response:

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

### HMIS HAZARD CLASSIFICATION

HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: B

### POTENTIAL HEALTH EFFECTS

EYES: MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

SKIN: MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

INGESTION: THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL TOXICITY.

INHALATION: NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO THE NOSE, THROAT OR MUCOUS MEMBRANES.

### HEALTH HAZARDS (ACUTE AND CHRONIC):

EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

### CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

### ADDITIONAL CARCINOGENICITY INFORMATION:

N/A

# SAFETY DATA SHEET



PRODUCT CODE: 36802

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT   | CAS NO.    | OSHA PEL | ACGIH TLV | OSHA STEL | WEIGHT % |
|--|------------|----------|-----------|-----------|----------|
| Modified Diglycidyl Ether of Bisphenol A           | 25068-38-6 | NONE     | NONE      | NONE      | 60-100   |
| Alkyl Glycidyl Ether                               | 68609-97-2 | NONE     | NONE      | NONE      | 10-30    |
| Siloxanes and Silicones, Di-Me Reactions           |            |          |           |           |          |
| Products with Silica (Non-Hazardous)               | 67762-90-7 | NONE     | NONE      | NONE      | 0.1-1    |
| Siloxanes and Silicones, Di-Methyl (Non-Hazardous) | 63148-62-9 | NONE     | NONE      | NONE      | 0.1-1    |

### SECTION 3 NOTES:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372 are present. \*\*\*

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

## SECTION 4: FIRST AID MEASURES

EYES: FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

SKIN: SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

INGESTION: LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, AND OTHERWISE DO NOT INDUCE VOMITING. IN EITHER CASE IMMEDIATELY CONSULT A PHYSICIAN.

INHALATION: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

## SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR  
(% by volume)                      UPPER: Not Available  
   LOWER: Not Available

FLASH POINT: 200+°F

METHOD USED: SETA FLASH

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO<sub>2</sub>, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NO UNUSUAL FIRE HAZARDS KNOWN.

## SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND PROTECTIVE CLOTHING SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

## SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN A COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

OTHER PRECAUTIONS:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CAN NOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

VENTILATION:

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

# SAFETY DATA SHEET



PRODUCT CODE: 36802

## EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

## WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCUPATIONAL EXPOSURE LIMIT VALUES.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID – AMBER CLEAR

BOILING POINT OR RANGE: 200+ °F

VAPOR DENSITY (AIR = 1): Not available

SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 1.1

EVAPORATION RATE: not available

SOLUBILITY IN WATER: NEGLIGIBLE

ODOR THRESHOLD: N/A

pH: N/A

MELTING POINT/FREEZING POINT: N/A

VAPOR PRESSURE: N/A

AUTO IGNITION TEMPERATURE: N/A

PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A

DECOMPOSITION TEMPERATURE: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO<sub>2</sub>, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

No data for the product itself.

Component data:

CAS# 25068-38-6: Moderate sensitizer, slight eye irritant, moderate skin irritant, Oral LD50 >5000 mg/kg (rat), Dermal LD50 >6000 mg/kg (rabbit)

CAS# 68609-97-2: possible sensitizer, eye and skin irritant, Oral LD50 >10000 mg/kg (rat), Inhalation LD50 – no microscopic changes

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data for the product itself.

Component data:

CAS# 25068-38-6: Biodegradability (Modified Sturm Method) 12%, Fish toxicity: Rainbow trout (96hr) LC50 1.5mg/l, Zebra Fish (96hr) LC50 2.4 mg/l.

Invertebrate Toxicity: Daphnia Toxicity (24hr) EC 50 3.6 mg/l

---

## SECTION 13: WASTE DISPOSAL

---

WASTE DISPOSAL METHOD: DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

---

## SECTION 14: TRANSPORT INFORMATION

---

DOT: Not Regulated

IMO/IMDG: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, MARINE POLLUTANT

# SAFETY DATA SHEET



PRODUCT CODE: 36802

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

Component data:

Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List.

Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.

EPA SARA Title III Section 313 components above the de minimus level: none

Component Siloxanes and silicones, di-me reactions products with silica: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component siloxanes and silicones, di-methyl: Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

---

## SECTION 16: OTHER INFORMATION

---

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**See Section 1 for date of preparation**

# SAFETY DATA SHEET



PRODUCT CODE: 36802

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TIGERGROUT HD PART B  
PRODUCT CODES: 36802

MANUFACTURER: Garon Products Inc.  
STREET ADDRESS: PO Box 1924  
CITY, STATE, ZIP: Wall, NJ 07719-1924

INFORMATION PHONE: 800-631-5380  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Polyamine mixture

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

GHS Classification: Skin corrosion/irritation category 1, skin sensitizer category 1B, serious eye damage category 1, acute hazard to aquatic environment category 3, chronic hazards to aquatic environment category 3

### GHS Label Elements and Precautionary Statements:

Label Elements: Exclamation Mark, Corrosion, Aquatic Toxicity

#### Hazard Statements:

Danger: Causes severe skin burns and eye damage

Warning: May cause an allergic skin reaction

Danger: Causes serious eye damage

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

#### Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection to prevent skin contact

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

#### Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P321 If skin irritation or burns develop, Call a doctor/physician.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P362 + P364 take off contaminated clothing and wash it before reuse

P310 If in eyes, immediately call a POISON CENTER or doctor/physician.

P391 Collect spillage

#### Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

### HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

### POTENTIAL HEALTH EFFECTS

EYES: WILL CAUSE BURNS TO THE EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE EYES.

SKIN: CAN CAUSE SKIN IRRITATION OR POSSIBLE BURNS TO THE SKIN

INGESTION: LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

INHALATION: HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA, AND DIZZINESS.

HEALTH HAZARDS (ACUTE AND CHRONIC):

PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS.

# SAFETY DATA SHEET



PRODUCT CODE: 36802

## CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

## ADDITIONAL CARCINOGENICITY INFORMATION:

NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT                        | CAS NO.    | OSHA PEL | ACGIH TLV | OSHA STEL | WEIGHT % |
|-----------------------------------|------------|----------|-----------|-----------|----------|
| Tetraethylene Pentamine           | 112-57-2   | NONE     | NONE      | NONE      | 7-13     |
| TOFA, Reaction Products with TEPA | 68953-36-6 | NONE     | NONE      | NONE      | 60-100   |

\*INDICATES TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

## SECTION 4: FIRST AID MEASURES

EYES: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN: FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION: DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.

## SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR  
(% by volume) UPPER: Not Available  
LOWER: Not Available

FLASH POINT: 200+°F

METHOD USED: SETA FLASH

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO<sub>2</sub>, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

## SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBENT AND PLACE IN DISPOSAL CONTAINERS.

## SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

OTHER PRECAUTIONS:

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

VENTILATION:

AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES – NEOPRENE OR RUBBER

EYE PROTECTION:

# SAFETY DATA SHEET



PRODUCT CODE: 36802

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCUPATIONAL EXPOSURE LIMIT VALUES.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE AND ODOR: AMBER CLEAR LIQUID WITH AMINE ODOR.

BOILING POINT OR RANGE: 155° TO 401°F

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 0.90

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

ODOR THRESHOLD: N/A

pH: N/A

MELTING POINT/FREEZING POINT: N/A

VAPOR PRESSURE: N/A

AUTO IGNITION TEMPERATURE: N/A

PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A

DECOMPOSITION TEMPERATURE: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID EXCESSIVE HEAT OR OPEN FLAMES.

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

CO<sub>2</sub>, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

No data for the product itself.

Component data:

Component CAS# 112-57-2: Ingestion LD50 > 1,230 mg/kg (rat)

Component CAS# 68953-36-6: Ingestion LD50 (rat) >2,000 mg/kg (estimated)

Component CAS# 68953-36-6 and CAS# 112-57-2: Skin LD50 (rabbit) 8,550 mg/kg. May cause eye irritation, skin irritation and may cause sensitization by contact

---

## SECTION 12: ECOLOGICAL INFORMATION

---

No data Available

---

## SECTION 13: WASTE DISPOSAL

---

WASTE DISPOSAL METHOD: DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

---

## SECTION 14: TRANSPORT INFORMATION

---

DOT: Not Regulated

IMO/IMDG : Not Regulated

# SAFETY DATA SHEET



PRODUCT CODE: 36802

---

## SECTION 15: REGULATORY INFORMATION

---

No data for the product itself.

Component data:

Component CAS# 68953-36-6: E20/22 Harmful by inhalation and if swallowed. On TSCA list, on DSL Canada, on EINECS, AICS, ENCS, ECL, SEPA, PICCS.

Component CAS# 112-57-2: OSHA hazard class – Irritant. Regulatory List: On TSCA, on EINECS, DSL, AICS, ENCS, ECL, SEPA, PICCS.

---

## SECTION 16: OTHER INFORMATION

---

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**See Section 1 for date of preparation**



# SAFETY DATA SHEET



PRODUCT CODE: 36802

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TIGERGROUT HD PART C  
PRODUCT CODES: 36802

MANUFACTURER: Garon Products Inc.  
STREET ADDRESS: PO Box 1924  
CITY, STATE, ZIP: Wall, NJ 07719-1924

INFORMATION PHONE: 800-631-5380  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 732-223-2002

DATE REVISED: 4/15/15

Chemical Name or Class: Sand

## SECTION 2: HAZARDS IDENTIFICATION

### Hazard Overview

GHS Classification: Carcinogenicity category 1, Specific target organ toxicity following repeated exposure category 1, Specific target organ toxicity (single exposure) category 3

GHS Label Elements and Precautionary Statements:

Label Elements: Health hazard, Exclamation Mark

### Hazard Statements:

DANGER: May cause cancer

DANGER: Causes damage to organs through prolonged or repeated exposures (lungs, respiratory system)

WARNING: May cause respiratory irritation.

### Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area.

### Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

### Storage:

P405 Store locked up

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

### Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

### HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: E

### POTENTIAL HEALTH EFFECTS

EYES: MAY CAUSE REDDENING OF THE EYES OR EYE IRRITATION FROM AIRBORNE PARTICLES.

SKIN: NONE KNOWN

INGESTION: NONE KNOWN

INHALATION: PROLONGED EXPOSURE TO RESPIRABLE CRYSTALLINE QUARTZ MAY CAUSE DELAYED LUNG INJURY (SILICOSIS). ACUTE OR RAPIDLY DEVELOPING SILICOSIS MAY OCCUR IN A SHORT PERIOD OF TIME IN HEAVY EXPOSURE IN SOME APPLICATIONS SUCH AS SAND BLASTING.

### HEALTH HAZARDS (ACUTE AND CHRONIC):

MAY CAUSE DELAYED SILICOSIS OR RAPID SILICOSIS IN SOME OCCUPATIONS SUCH AS SANDBLASTING, SILICOSIS IS A FORM OF A DISABLING PULMONARY FIBROSIS WHICH CAN BE PROGRESSIVE AND COULD LEAD TO DEATH. INHALATION MAY LEAD TO LUNG SCARRING AND MASSIVE FIBROSIS WHICH COULD BE ACCOMPANIED BY RIGHT HEART ENLARGEMENT, HEART FAILURE, OR PULMONARY FAILURE, SMOKING AGGRAVATES THE EFFECTS OF EXPOSURE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS CAN BE AGGRAVATED BY EXPOSURE

### CARCINOGENICITY

OSHA: NO NTP: YES IARC: YES

ADDITIONAL CARCINOGENICITY INFORMATION:

# SAFETY DATA SHEET



PRODUCT CODE: 36802

IARC HAS DETERMINED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ IS CARCINOGENIC TO HUMANS (GROUP 1- CARCINOGENIC TO HUMANS). THE NTP CLASSIFIES RESPIRABLE CRYSTALLINE SILICA AS REASONABLY ANTICIPATED TO BE A CARCINOGEN.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT      | CAS NO.    | OSHA PEL            | ACGIH TLV           | OSHA STEL           | WEIGHT % |
|-----------------|------------|---------------------|---------------------|---------------------|----------|
| Silicon Dioxide | 14808-60-7 | 10mg/m <sup>3</sup> | .1mg/m <sup>3</sup> | .1mg/m <sup>3</sup> | 100      |

### SECTION 2 NOTES:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

FOLLOW OSHA HAZARD COMMUNICATION RULE 29CFR SECTIONS 1910.1200, 1915.99, 1917.28, 1918.9, 1926.59, AND STATE AND LOCAL COMMUNITY RIGHT TO KNOW LAWS. WE RECOMMEND THAT SMOKING BE PROHIBITED IN AREAS WHERE RESPIRATORS MUST BE USED.

## SECTION 4: FIRST AID MEASURES

EYES: FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN IF CONDITIONS WARRANT.

SKIN: SKIN CONTACT WILL NORMALLY CAUSE NO HEALTH RISKS

INGESTION: IF INGESTED, CONSULT A PHYSICIAN

INHALATION: REMOVE VICTIM TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

## SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR  
(% by volume) UPPER: Not Available  
LOWER: Not Available

FLASH POINT °F: N/A

METHOD USED: N/A

EXTINGUISHING MEDIA: OTHER

SPECIAL FIRE FIGHTING PROCEDURES:

CRYSTALLINE SILICA IS NEITHER A FIRE NOR AN EXPLOSION HAZARD

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE KNOWN.

## SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR RESPIRATOR AND USE DUSTLESS HANDLING EQUIPMENT TO CLEAN UP LARGE SPILLS, PLACE IN SUITABLE CONTAINERS FOR DISPOSAL. FLUSH AREA WITH WATER AFTER PICKUP OF MATERIAL.

## SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

STORE IN COOL DRY PLACE. PROPERLY LABEL ALL CONTAINERS AND RESEAL ALL PARTIALLY USED CONTAINERS. AVOID CREATING ANY DUST WHEN WORKING WITH THIS MATERIAL.

OTHER PRECAUTIONS:

AVOID BREATHING DUST GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. PROVIDE TRAINING FOR YOUR EMPLOYEES RELATING TO OCCUPATIONAL EXPOSURE TO QUARTZ DUST. SEE ASTM STANDARD E1132-86 STANDARD PRACTICE FOR HEALTH REQUIREMENTS RELATING TO EXPOSURE TO QUARTZ DUST. IF BETTER THAN 500 X PEL USE A SELF CONTAINED BREATHING APPARATUS. IF SANDBLASTING, USE ANY TYPE CE SUPPLIED AIR RESPIRATOR WITH FULL FACE PIECE OR HOOD.

Safety phrases

S22 Do not breathe dust

S25 Avoid contact with eyes

S38 In case of insufficient ventilation wear suitable respiratory equipment

S39 Wear eye/face protection

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO QUARTZ DUST. PROVIDE SUFFICIENT EXHAUST TO KEEP EXPOSURE LEVELS BELOW THE ACGIH PEL.

VENTILATION:

# SAFETY DATA SHEET



PRODUCT CODE: 36802

USE EXHAUST SUFFICIENT TO MAINTAIN AIRBORNE PARTICULATES BELOW THE ACGIH PEL LIMITS ESTABLISHED.

PROTECTIVE GLOVES:

N/A

EYE PROTECTION:

SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

PROVIDE ANY EQUIPMENT NECESSARY TO PREVENT THE INHALATION OF QUARTZ DUST.

WORK HYGIENIC PRACTICES:

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

SEE SECTION THREE FOR OCCUPATIONAL EXPOSURE LIMIT VALUES

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE AND ODOR: WHITE OR TAN SAND GRANULAR CRUSHED OR GROUND- NO ODOR

BOILING POINT OR RANGE °F: N/A

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 2.6

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: INSOLUBLE IN WATER

ODOR THRESHOLD: N/A

pH: N/A

MELTING POINT/FREEZING POINT: N/A

VAPOR PRESSURE: N/A

AUTO IGNITION TEMPERATURE: N/A

PARTITION COEFFICIENT: N-OCTANOL/WATER: N/A

DECOMPOSITION TEMPERATURE: N/A

---

## SECTION 10: STABILITY AND REACTIVITY

---

STABILITY: STABLE

CONDITIONS TO AVOID (STABILITY):

CONTACT WITH POWERFUL OXIDIZING AGENTS SUCH AS FLUORINE, CHLORINE, TRIFLUORIDE, MANGANESE TRIOXIDE, OXYGEN TRIFLUORIDE

INCOMPATIBILITY (MATERIAL TO AVOID):

CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS- SEE CONDITIONS TO AVOID

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SILICA WILL DISSOLVE IN HYDROCHLORIC ACID TO FORM A CORROSIVE GAS- SILICON TETRAFLUORIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

Silicon dioxide: Inhalation and retention of respirable crystalline silica can cause silicosis in several forms, chronic, accelerated or acute. Acute silicosis can occur with exposures to high concentrations of respirable crystalline silica over a very short time period, the symptoms of acute silicosis include progressive shortness of breath, fever, cough, and weight loss. Acute silicosis can be fatal. IARC concluded that there was sufficient evidence in humans for the carcinogenicity of crystalline silica in the form of quartz (Group 1). Exposure to respirable crystalline silica can also be associated with autoimmune disease, tuberculosis, kidney damage, non-malignant respiratory disease. For further information, the NIOSH Hazard Review- Occupational Effects of Occupational Exposure to Respirable Crystalline Silica published in April of 2002 should be reviewed.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

Silicon Dioxide: There is no data that suggests that crystalline silica is toxic to birds, fish, invertebrates, microorganisms or plants.

---

## SECTION 13: WASTE DISPOSAL

---

WASTE DISPOSAL METHOD: DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

---

## SECTION 14: Transport Information

---

DOT: Not Regulated

IMO/IMDG Not regulated

# SAFETY DATA SHEET



PRODUCT CODE: 36802

---

## SECTION 15: REGULATORY INFORMATION

---

Silicon Dioxide: risk phrases: R 48/20 Harmful – Danger of serious damage to health by prolonged exposure through inhalation. Safety Phrases: S 22 – Do not breathe dust and S 38 – In case of insufficient ventilation, wear suitable respiratory equipment

Crystalline Silica (Silicon Dioxide) is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act list as toxic, Pennsylvania Worker and community right to know Act list as a hazardous substance.

Crystalline Silica (Silicon Dioxide) is on the Canada DSL – WHMIS Classification D2A

Crystalline Silica is on the Australian Inventory of Chemicals Substances list, Japan Ministry of International Trade and Industry list, Korea Existing Chemicals Inventory with registry number 9212-5667 and the Philippines Inventory of Chemicals and Chemical Substances list.

---

## SECTION 16: OTHER INFORMATION

---

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, however, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

**N/A = Not Available**

**See Section 1 for date of preparation**